

Datenblatt



SFL 90°



Flansch-Schlaucharmatur

Abdichtung: durch Flansch und Profildichtring

Baureihe: leichte Baureihe 3000 PSI

Flanschgröße in Zoll

Material: Stahl verzinkt

Zolltarifnummer: 73079100

Beispielhaftes Modell

Artikelnummer	DN	Flanschgröße (in Zoll)	Betriebsdruck (in bar)	AD (in mm)	H (in mm)
1.470-08-06	10	1/2"	350	30,2	6,8
1.470-08-08	12	1/2"	350	30,2	6,8
1.470-08-10	16	1/2"	350	30,2	6,8
1.470-08-12	19	1/2"	350	30,2	6,8
1.470-10-08	12	5/8"	350	34,0	6,8
1.470-10-10	16	5/8"	350	34,0	6,8
1.470-10-12	19	5/8"	350	34,0	6,8
1.470-12-08	12	3/4"	350	38,1	6,8
1.470-12-10	16	3/4"	350	38,1	6,8
1.470-12-12	19	3/4"	350	38,1	6,8
1.470-12-16	25	3/4"	280	38,1	6,8
1.470-16-08	12	1"	350	44,5	8,0
1.470-16-12	19	1"	350	44,5	8,0
1.470-16-16	25	1"	280	44,5	8,0

1.470-16-20	31	1"	210	44,5	8,0
1.470-20-16	25	1 1/4"	280	50,8	8,0
1.470-20-20	31	1 1/4"	210	50,8	8,0
1.470-20-24	38	1 1/4"	206	50,8	8,0
1.470-24-20	31	1 1/2"	210	60,3	8,0
1.470-24-24	38	1 1/2"	185	60,3	8,0
1.470-24-32	50	1 1/2"	170	60,3	8,0
1.470-32-24	40	2"	185	71,4	9,6
1.470-32-32	51	2"	170	71,4	9,6
1.470-40-32	51	2 1/2"	170	84,1	9,6
1.470-40-40	63	2 1/2"	69	84,1	9,6
1.470-48-48	76	3"	50	101,6	9,6

Die Angaben können je Artikel leichte Abweichungen enthalten.

Klement Hydraulik

Ketten - Seile - Hydraulik

06028 - 40 625 62

klement.j@t-online.de